

SAFETY DATA SHEET

TRL110 – BLAC TYRE MOUNTING PASTE 5Kg

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

Product name TRL110– BLACK TYRE MOUNTING PASTE 5kg
Company Autogem Motor Concepts LLP
 Unit 6 Space Business Park
 Abbey Road
 London
 NW10 7SU
 United Kingdom
 sales@autogem.co.uk
 www.AUTOGEM.CO.UK

Tel +44 (0) 20 8838 0910
Fax +44 (0) 20 8838 1854

2. COMPOSITION / INFORMATION ON INGREDIENTS

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Mono ethylene glycol (Ethane-1,2-diol particulate)	603-027-00-1	107-21-1	203-473-3			Xn; R22

3. HAZARDS IDENTIFICATION

No Significant Hazard

4. FIRST AID MEASURES

- Inhalation** Irritating to respiratory system. Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Move the exposed person to fresh air. Seek medical attention.
- Eye contact** Irritating to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
- Skin contact** Irritating to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
- Ingestion** Ingestion may cause nausea and vomiting. Seek medical attention if irritation or symptoms persist.

5. FIRE FIGHTING MEASURES

- Extinguishing media** Carbon dioxide (CO2).
- Special hazards** Burning produces irritating, toxic and obnoxious fumes.
- Advice for fire-fighters** Wear suitable respiratory equipment when necessary.

6. ACCIDENTAL RELEASE MEASURES

Personal precaution	Avoid raising dust. Ensure adequate ventilation of the working area. Wear suitable protective equipment.
Environmental precautions	Do not allow product to enter drains. Prevent further spillage if safe.
Cleaning up	Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

7. HANDLING AND STORAGE

Handling	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.
Storage	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limit Values

Mono ethylene glycol (Ethane-1, 2-diol particulate)	WEL 8-hr limit ppm: - WEL 15 min limit ppm: -	WEL 8-hr limit mg/m ³ :10 WEL 15 min limit mg/m ³ :-
Mono ethylene glycol (Ethane-1, 2-diol vapour)	WEL 8-hr limit ppm: 20 WEL 15 min limit ppm: 40	WEL 8-hr limit mg/m ³ :52 WEL 15 min limit mg/m ³ :104

Appropriate engineering controls	Ensure adequate ventilation of the working area.
Individual protection measures	Wear chemical protective clothing.
Eye / face protection	Approved safety goggles.
Skin /Hand protection	Chemical resistant gloves (PVC).
Respiratory protection Wear:	Suitable respiratory equipment.

9. PHYSICAL AND CHEMICAL PROPERTIES

State	Solid
Colour	Black
Odour	Odourless

10. STABILITY AND REACTIVITY

Stable under normal conditions.

11. TOXICOLOGICAL INFORMATION

No known adverse health effects.

12. ECOLOGICAL INFORMATION

No known adverse environmental effects.

13. DISPOSAL CONSIDERATIONS

Dispose of in compliance with all local and national regulations.

14. TRANSPORT INFORMATION

The product is not classified as dangerous for carriage.

15. REGULATORY INFORMATION

No Significant Hazard.

16. OTHER INFORMATION

R22 - Harmful if swallowed.

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. As the application of products is outside our control, the information is given without legal responsibility. Customers should test under their own conditions to ensure the products are suitable for their own requirements.